## What is claimed is:

5

15

25

30

35

1. A method of analyzing flutter test data, the method comprising:

reading a plurality of data points, each data point representing an amplitude versus a test time;

determining a number "N" of damped sine waves to fit to the plurality of data points; and

fitting the number "N" of damped sine waves to the plurality of data points.

- 2. The method of Claim 1, wherein fitting the number "N" of damped sine waves to the plurality of data points includes fitting the number "N" of damped sine waves to the plurality of data points using a non-linear "N" damped sine wave fitting algorithm.
  - 3. The method of Claim 1, wherein determining a number "N" of damped sine waves to fit to the plurality of data points includes comparing a magnitude of a time history response for a sine wave mode to a total transducer response.
  - 4. The method of Claim 1, wherein determining a number "N" of damped sine waves to fit to the plurality of data points includes:

determining a fit error between a candidate sine wave mode and the plurality of data points; and

comparing a magnitude of a time history response for the candidate sine wave mode to the fit error.

5. The method of Claim 1, wherein fitting the number "N" of damped sine waves to the plurality of data points includes:

determining a fit error between a sine wave mode and the plurality of data points; and

applying a Fast-Fourier Transform function to the fit error to estimate a next sine wave mode to be included in the non-linear "N" damped sine wave fitting algorithm.

6. The method of Claim 1, wherein fitting the number "N" of damped sine waves to the plurality of data points includes:

assessing a significance of a sine wave mode; and

determining whether to include the sine wave mode in the non-linear "N" damped sine wave fitting algorithm based on the assessment.

25315
PATENT TRADEMARK OFFICE

- 12 -

BLACK LOWE & GRAHAM \*LC

816 Second Avenue Seartle, Washington 98104 206.381.3300 • F: 206.381.3301

BOEI-1-1185AP.doc

- The method of Claim 6, wherein assessing a significance of a sine wave mode 7. includes determining an amplitude factor for the sine wave mode.
- 8. 5 The method of Claim 6, wherein assessing a significance of a sine wave mode includes determining an amplitude factor for the sine wave mode, the amplitude factor being a function of a ratio of an amplitude over an amplitude range of the sine wave mode.
- 9. The method of Claim 8, wherein assessing a significance of a sine wave mode further includes determining the sine wave mode to be insignificant when the amplitude 10 factor is less than or approximately equal to an average error value.
  - The method of Claim 8, wherein assessing a significance of a sine wave mode further includes determining the sine wave mode to be insignificant when the amplitude factor is less than or approximately equal to a square root of an average error value squared.
    - 11. The method of Claim 1, wherein reading a plurality of data points includes: reading a first plurality of data points corresponding to a first test sensor; and reading a second plurality of data points corresponding to a second test sensor.

20

15

12. A method of analyzing flutter test data, the method comprising:

reading a plurality of sets of data points obtained from a plurality of test sensors, each set of data points representing an amplitude versus a test time for a corresponding one of the plurality of test sensors;

25 determining which of the plurality of sets of data points are useful sets of data points;

> for the useful sets of data points, performing a curve fit that includes determining a number "N" of damped sine waves to fit to the useful sets of data points; and fitting the number "N" of damped sine waves to the useful sets of data points.

30

The method of Claim 12, wherein fitting the number "N" of damped sine waves to the plurality of data points includes fitting the number "N" of damped sine waves to the plurality of data points using a non-linear "N" damped sine wave fitting algorithm.



- 13 -

816 Second Avenue

BLACK LOWE & GRAHAM PLLC

BOEI-1-1185AP.doc

Seartle, Washington 98104 206.381.3300 • F: 206.381.3301

- 14. The method of Claim 12, wherein determining a number "N" of damped sine waves to fit to the useful sets of data points includes comparing a magnitude of a time history response for a sine wave mode to a total transducer response.
- 15. The method of Claim 12, wherein determining a number "N" of damped sine waves to fit to the useful sets of data points includes:

determining a fit error between a candidate sine wave mode and the useful sets of data points; and

comparing a magnitude of a time history response for the candidate sine wave mode to the fit error.

16. The method of Claim 12, wherein fitting the number "N" of damped sine waves to the useful sets of data points includes:

determining a fit error between a sine wave mode and the useful sets of data points;

applying a Fast-Fourier Transform function to the fit error to estimate a next sine wave mode to be included in the non-linear "N" damped sine wave fitting algorithm.

17. The method of Claim 12, wherein fitting the number "N" of damped sine waves to the useful sets of data points includes:

assessing a significance of a sine wave mode; and

determining whether to include the sine wave mode in the non-linear "N" damped sine wave fitting algorithm based on the assessment.

- 25 18. The method of Claim 17, wherein assessing a significance of a sine wave mode includes determining an amplitude factor for the sine wave mode.
  - 19. The method of Claim 17, wherein assessing a significance of a sine wave mode includes determining an amplitude factor for the sine wave mode, the amplitude factor being a function of a ratio of an amplitude over an amplitude range of the sine wave mode.
    - 20. The method of Claim 19, wherein assessing a significance of a sine wave mode further includes determining the sine wave mode to be insignificant when the amplitude factor is less than or approximately equal to an average error value.

35

30

5

15

20

and



- 14 -

BLACK LOWE & GRAHAM PLLC

816 Second Avenue Seattle, Washington 98104 206.381.3300 • F: 206.381.3301

BOEI-1-1185AP.doc

- 21. The method of Claim 19, wherein assessing a significance of a sine wave mode further includes determining the sine wave mode to be insignificant when the amplitude factor is less than or approximately equal to a square root of an average error value squared.
- 5 22. The method of Claim 12, wherein fitting the number "N" of damped sine waves to the useful sets of data points includes:

determining an error value for each useful data set; and scaling the useful data set to evenly weight the fit for each useful data set.

23. A machine-readable medium having instructions stored thereon for execution by a processor to perform a method of of analyzing flutter test data, the method comprising:

reading a plurality of data points, each data point representing an amplitude versus a test time;

determining a number "N" of damped sine waves to fit to the plurality of data points; and

fitting the number "N" of damped sine waves to the plurality of data points.

- 24. The medium of Claim 23, wherein fitting the number "N" of damped sine waves to the plurality of data points includes fitting the number "N" of damped sine waves to the plurality of data points using a non-linear "N" damped sine wave fitting algorithm.
  - 25. The medium of Claim 23, wherein determining a number "N" of damped sine waves to fit to the plurality of data points includes comparing a magnitude of a time history response for a sine wave mode to a total transducer response.
  - 26. The medium of Claim 23, wherein determining a number "N" of damped sine waves to fit to the plurality of data points includes:

determining a fit error between a candidate sine wave mode and the plurality of data points; and

- comparing a magnitude of a time history response for the candidate sine wave mode to the fit error.
  - 27. The medium of Claim 23, wherein fitting the number "N" of damped sine waves to the plurality of data points includes:

25315
PATENT TRADEMARK OFFICE

20

25

30

- 15 -

BLACK LOWE & GRAHAM \*\*\*\*

816 Second Avenue Seattle, Washington 981

Seattle, Washington 98104 206.381.3300 • F: 206.381.3301 determining a fit error between a sine wave mode and the plurality of data points; and

applying a Fast-Fourier Transform function to the fit error to estimate a next sine wave mode to be included in the non-linear "N" damped sine wave fitting algorithm.

5

28. The medium of Claim 23, wherein fitting the number "N" of damped sine waves to the plurality of data points includes:

assessing a significance of a sine wave mode; and
determining whether to include the sine wave mode in the non-linear "N" damped
sine wave fitting algorithm based on the assessment.

- 29. The medium of Claim 28, wherein assessing a significance of a sine wave mode includes determining an amplitude factor for the sine wave mode.
- 30. The medium of Claim 28, wherein assessing a significance of a sine wave mode includes determining an amplitude factor for the sine wave mode, the amplitude factor being a function of a ratio of an amplitude over an amplitude range of the sine wave mode.
- 31. The medium of Claim 30, wherein assessing a significance of a sine wave mode further includes determining the sine wave mode to be insignificant when the amplitude factor is less than or approximately equal to an average error value.
  - 32. The medium of Claim 30, wherein assessing a significance of a sine wave mode further includes determining the sine wave mode to be insignificant when the amplitude factor is less than or approximately equal to a square root of an average error value squared.
    - 33. The medium of Claim 23, wherein reading a plurality of data points includes: reading a first plurality of data points corresponding to a first test sensor; and reading a second plurality of data points corresponding to a second test sensor.

30

25

34. A system for analyzing flutter test data, comprising: a control component;

25315
PATENT TRADEMARK OFFICE

- 16 -

BLACK LOWE & GRAHAM \*\*\*\*

BOEI-1-1185AP,doc Sear

816 Second Avenue Seartle, Washington 98104 206,381,3300 • F: 206,381,3301 a computer operatively coupled to the control component and adapted to receive a plurality of test data points, the computer further being adapted to perform a method of analyzing the plurality of test data points, the method including:

determining a number "N" of damped sine waves to fit to the plurality of data points; and

fitting the number "N" of damped sine waves to the plurality of data points.

- 35. The system of Claim 34, wherein fitting the number "N" of damped sine waves to the plurality of data points includes fitting the number "N" of damped sine waves to the plurality of data points using a non-linear "N" damped sine wave fitting algorithm.
  - 36. The system of Claim 34, wherein fitting the number "N" of damped sine waves to the plurality of data points includes:

determining a fit error between a sine wave mode and the plurality of data points; and

applying a Fast-Fourier Transform function to the fit error to estimate a next sine wave mode to be included in the non-linear "N" damped sine wave fitting algorithm.

20 37. The system of Claim 34, wherein fitting the number "N" of damped sine waves to the plurality of data points includes:

assessing a significance of a sine wave mode; and

determining whether to include the sine wave mode in the non-linear "N" damped sine wave fitting algorithm based on the assessment.

- 38. The system of Claim 34, wherein the plurality of test data points include a first plurality of test data points from a first test sensor, and wherein the computer module is further adapted to receive a second plurality of test data points from a second test sensor.
- 30 39. The system of Claim 34, wherein the computer includes a central processing unit and a memory component.
  - 40. The system of Claim 34, wherein the computer includes an I/O component.



5

15

25

- 17 -

BLACK LOWE & GRAHAM PLLC

BOEI-1-1185AP.doc

816 Second Avenue Seattle, Washington 98104 206.381,3300 • F: 206.381,3301

- 41. The system of Claim 34, further comprising a data acquisition component operatively coupled to at least one of the computer and the control component.
- 42. The system of Claim 41, wherein the data acquisition component includes a plurality of data acquisition sensors.

10



- 18 -

BLACK LOWE & GRAHAM PLIC

BOEI-1-1185AP.doc

816 Second Avenue Seartle, Washington 98104 206.381.3300 • F: 206.381.3301